RADIOCHEMISTRY
List of Acronyms

A	*Standard Methods*	*NERHL*	*North Eastern Health Radiological Laboratory*
ASTM	*American Society for Testing & Materials*	*NORM*	*Naturally Occurring Radioactive Materials*
E or EPA	*US Environmental Protection Agency*	*MDC*	*Minimum Detection Concentration*
HNO_3	*Nitric Acid*	*SW*	*Solid Waste – 846*
LAACC	*Large Area Activated Charcoal Canister*	*TSP*	*Total Suspended Particulate*
HASL	*Health and Safety Laboratory*	*USNRC*	*U.S. Nuclear Regulatory Commission*

RADIOCHEMISTRY

1. MATRIX DIGESTIONS – Prior to analysis

MATRIX	PREPARATION TECHNIQUE	AMOUNT OF SAMPLE REQUIRED
Drinking Water	HNO_3 to pH <2	1000 mL plastic
Drinking Water – ^{222}Radon	None Required	40 mL VOA vial – no headspace
Mine and Process Water – Soluble Constituents	Filtration, HNO_3 to pH <2	2000 mL plastic
Mine and Process Water – Total Constituents	HNO3 to pH <2	2000 mL plastic
Solids – Core, Sediments, Sludges, Soils, Rock	Acid Digestion	100 g
Vegetation – USNRC Guidelines	Ashing, Acid Digestion	20 Kg
Biomass – USNRC Guidelines	Ashing, Acid Digestion	20 Kg
Air Filters	Acid Leaching	Filter sample and blank filter
Oils	Acid Leaching	100 g
Sample Preparation	Drying, Pulverizing	500 g
Sample Preparation	Canning	500 g

2. RADIOCHEMICAL ANALYSES – Drinking Water

ANALYSIS	METHOD	Drinking Water MCL	MIN. REQUIRED REPORTING LIMIT	UNITS
Gamma Emitting Radionuclides	E901.1	NA	dependent on sample size	pCi/L
Gross Alpha and Beta Radioactivity	E900.0	15/50 (see note)	3.0/4.0	pCi/L
Gross Radium Alpha (minus Radon & Uranium)	E900.1	15	3	pCi/L
^{226} Radium (Alpha Emitting Isotopes)	E903.0	5.0 (see note)	1	pCi/L
^{228} Radium (Beta Emitting Isotopes)	RA-05	5.0 (see note)	1	pCi/L
^{222} Radon	ASTM D5072-92	NA	100	pCi/L
Isotopic Uranium (^{234}U, ^{235}U, ^{238}U)	E908.0	NA	0.67	pCi/L
Uranium	E200.8	30	1	ug/L
Sample Location: Entry point to distribution				
Notes: Gross Beta Activity MCL = 4 mRem/year ~ = 50 pCi/L. Regulation specifies monitoring for vulnerable systems. The Radium MCL is for a combined Radium 226+Radium 228 = 5.0 pCi/L.				

RADIOCHEMISTRY

3. RADIOCHEMICAL ANALYSES - Applicable to most matrices listed above (after digestion)

Reporting Limits are matrix dependent

ANALYSIS	METHOD	MIN. REQUIRED REPORTING LIMIT	UNITS
Gamma Emitting Radionuclides	E901.1	dependent on sample size	pCi/L
Gross Alpha and Beta Radioactivity	E900.0	1.0/2.0	pCi/L
Gross Radium Alpha (minus Radon & Uranium)	E900.1	1	pCi/L
^{210} Lead	E909.0	1	pCi/L
^{210} Polonium	HASL-300 Po-02-RC	1	pCi/L
^{40} Potassium	E901.1	dependent on sample size	pCi/L
^{226} Radium (Alpha Emitting Isotopes)	E903.0	0.2	pCi/L
^{228} Radium (Beta Emitting Isotopes)	RA-05	1	pCi/L
^{222} Radon	ASTM D5072-92	100	pCi/L
Isotopic Thorium (^{228}Th, ^{230}Th, ^{232}Th)	E908.0	0.2 per Isotope	pCi/L
^{232} Thorium	E200.8/SW6020	1	pCi/L
Isotopic Uranium (^{234}U, ^{235}U, ^{238}U)	A7500-U-C	0.2 per Isotope	pCi/L
Uranium, natural	E200.8/SW6020	0.2	pCi/L
Uranium, natural – low level	E200.8/SW6020	-	pCi/L

4. BIOASSAY - Uranium and other radionuclides in urine per USNRC Guideline 8.22.

ANALYSIS	REQUIRED VOLUME, mL	QC REQUIRED	MIN. REQUIRED REPORTING LIMIT	UNITS
Isotopic Uranium	1000 plastic	client specific	0.1	pCi/L
Uranium	100 plastic	25%	5	µg/L

RADIOCHEMISTRY

5. RADIOLOGICAL FIELD SERVICES

SERVICE	
Radon - inside air by charcoal canister method (Ramses II Detector)	by Quote
Consulting Radiation Safety Officer – USNRC Accepted	by Quote
Surface Gamma Surveys - baseline, decontamination and decommissioning, process operations	by Quote
Air Quality Sampling - TSP, High Volume Air Sampling	by Quote
Equipment Decontamination and Release Surveys	by Quote
Emanation Coefficient	by Quote
Naturally Occurring Radioactive Materials (NORM) Surveys – oilfield related	by Quote
Large Area Activated Charcoal Canister (LAACC) Tailings Surveys - Radon Flux by Method E115	by Quote
Indoor Radon and Radon Progeny Measurements – Single or Multiple Site	by Quote
Custom Radiation Safety Courses - mining, milling, and reclamation projects	by Quote